




Green Pin® Sling Hook E S/S-GR5

Grade 5 stainless steel eye sling hook

- **Material:** AISI 316L, grade 5
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** polished
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI[®]



CSOI



for chain diameter		working load limit	length	diameter inside eye	width opening	thickness	width	diameter eye outside	width outside	length	width	thickness	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
6	⁷ / ₃₂	0.7	84	23	26	15	20	43	72	114	10	6	0.28
7 - 8	¹ / ₄ - ⁵ / ₁₆	1.2	103	26	30	20	24	51	87	139	12	8	0.56
10	³ / ₈	1.6	128	35	33	24	29	65	106	172	15	10	1.09
13	¹ / ₂	2.7	152	41	37	32	39	77	133	209	18	12	1.98




Green Pin® Sling Hook CL S/S-GR5

Grade 5 stainless steel clevis sling hook

- **Material:** AISI 316L, grade 5
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** polished
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI[®]



CSCI



for chain diameter		working load limit	length	width	width opening	thickness	width	width outside	width outside	length	diameter pin	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
5	³ / ₁₆	0.5	76	7	26	15	20	28	72	108	6	0.29
6	⁷ / ₃₂	0.7	75	7	26	15	20	28	72	108	8	0.29
7 - 8	¹ / ₄ - ⁵ / ₁₆	1.2	95	9	30	20	24	32	87	136	9	0.58
10	³ / ₈	1.6	113	12	33	24	29	42	106	164	13	1.1
13	¹ / ₂	2.7	138	15	37	32	39	54	133	208	16	1.86